



## DUST TROL 230

DUST CONTROL ADDITIVE

### Description

Best-Chem's DUST TROL 230 is a product containing wetting agents used to control dust in the unloading, transfer, and storage of coal, aggregate, fly ash, and other friable materials.

### Application

Product should be diluted with water and applied as foam through Best-Chem's dosing equipment to maximize product distribution and dust control effectiveness.

Recommended application rate is based on the particle size and moisture content of the mineral as well as desired reduction in opacity.

Consult your Best-Chem representative for application rates for your specific application.

### Typical Properties

pH (conc.) @ 25°C (ASTM E-70) 9.0  
Density @ 25°C (ASTM D-287) 8.4 lbs/gal  
Appearance Yellow Liquid  
Viscosity (cps @ 77°F) 20-40  
Specific Gravity 1.03  
Flash Point >200°F (93.3°C)  
Freeze Point 28°F (-2.2°C)

### Handling, Storage & Safety

Product may be stored in high-density polyethylene lined drums and in polypropylene, fiberglass, polyethylene, or epoxy-lined tanks. Product is a moderate skin and eye irritant. Eye protection such as chemical goggles should be worn whenever splashing, spraying, or other eye contact is possible.

Wear impervious (rubber or neoprene) gloves when handling product. Refer to MSDS for detailed handling precautions.

*BEST-CHEM LTD. IS AN ISO 9002 REGISTERED FIRM.*

**Barracks Road, Sandy Lane Industrial Estate, Stourport on Severn, Worcs.DY13 9QB**

**Tel 01299 827232 Fax 01299 827608**

**[www.best-chem.co.uk](http://www.best-chem.co.uk)**

**[info@best-chem.co.uk](mailto:info@best-chem.co.uk)**