

# TECHNICAL DATA SHEET

# EXIT

## STRIPPER FOR FLOOR POLISH & WAX

**COMPOSITION:** EXIT is a specially designed floor stripper that is a unique blend of surfactants, solvents and special chelating agents which synergise for a quick and safe removal of all high solid floor finishes and waxes.

**BENEFITS:** Formulated to remove high solids, floor polishes and wax.  
Safe to use on rubber, asphalt, vinyl linoleum, vinyl asbestos and terrazzo.  
Can be used hot. No emission of Ammonia fumes.  
Low foaming and odourless. Do not use on glass, may etch.

**DIRECTIONS FOR USE:** **TO REMOVE POLISH AND LEAVE FLOOR SEALER**

- 1) Dilute 1 part **EXIT** to 10 parts hot/cold water.
- 2) Spread solution liberally on floor (100sq.ft). Soak for 5-10 minutes until surface goes milky in appearance.
- 3) Scrub thoroughly using black pad. Remove stripping solution by mop or vacuum, never let dry onto the floor.
- 4) Rinse with clear water. Allow to dry. If any film remains, a second rinse is required.

**TO REMOVE FLOOR SEALER:**

- 1) Dilute 1 part **EXIT** to 4 parts warm water and follow steps as above. To remove a heavy build-up of seal, a build-up removal abrasive pad may be needed. Use carefully to void scratching vinyl surfaces.

**SPECIFICATIONS:**

Appearance	-	Clear white liquid
Odour	-	Slight Odour
Specific Gravity	-	1.06
pH	-	>12
Safety	-	Completely safe when used as directed

**CAUTION:** **EXIT IS A STRONG ALKALINE LIQUID.**  
Irritating to eyes and skin.  
Avoid excessive skin contact.  
For splashes on the skin and eyes wash thoroughly with cold water.  
**KEEP FROM FREEZING.**

*BEST-CHEM LTD. IS AN ISO 9002 REGISTERED FIRM.*