

# TECHNICAL DATA SHEET

# ODOUR CAP

## FLOATING LIFT STATION DEGREASER AND INSTANT ODOUR CAP

**COMPOSITION:** ODOUR CAP is a blend of natural citrus derived Terpinenes and Aliphatic Solvents.

**BENEFITS:** CAPS objectionable odours instantly.

**DISSOLVES** grease and slime in lift stations, septic tanks, cesspools and grease traps.

**FLOATS** on water thereby trapping smells.

**IMPROVES** Lift Station efficiency.

**NATURALLY** based degreaser.

**BIODEGRADABLE:** Will not affect waste plant.

### **DIRECTIONS FOR USE:**

#### **LIFT STATIONS:**

Pour directly into manhole or lift station pit. For best results use sufficient quantity to assure a 1-3 inch cap on the surface. (EXAMPLE: To create a 1 inch cap on a 6 foot diameter lift station - add 20 gallons).

#### **SEPTIC TANKS AND CESSPOOLS:**

Add 1 litre per 5000 gallons capacity for initial treatment. Use 20 - 50 mls.per week for each 500 gallons capacity as a Preventative Maintenance treatment.

#### **GREASE TRAPS:**

Pour 100 mls. (Half cup) of concentrate into drains. Allow to remain overnight. Repeat as necessary.

**SPECIFICATION:**

Appearance	-	Clear pale liquid
Odour	-	Citrus odour
Specific Gravity	-	0.85
Flash point	-	40 <sup>0</sup> C Closed cup

### **CAUTION:**

**ODOUR CAP IS A FLAMMABLE LIQUID.**

Protective gloves and goggles are recommended.

For splashes, wash liberally with cold water.

***BEST-CHEM LTD. IS AN ISO 9002 REGISTERED FIRM.***