

TECHNICAL DATA SHEET

TAG

COMPOSITION: TAG comprises of an emulsifiable solvent suitable for removing tar, asphalt, grease, oil and grime.

BENEFITS: Rapid acting tar solvent.
Safe on all metals.
Suitable for cleaning road machinery trucks tools, concrete and industrial equipment.

DIRECTIONS FOR USE:

- TO REMOVE TAR AND ASPHALT:**
- 1) Spray neat TAG on a 10-ft. square area.
 - 2) Allow to soak for 5 minutes to penetrate and dissolve tar.
 - 3) Rinse off with pressure water hose.
 - 4) For stubborn areas scrub with brush prior to hosing.

- TO REMOVE GREASE, OIL AND GRIME:**
- 1) TAG can be diluted 1 part TAG with up to 10 parts paraffin or white spirits.
 - 2) This solution is then sprayed or brushed on the soil to be removed.
 - 3) Allow to soak for 5 minutes, then rinse off with pressure water.

NOTE: **DO NOT USE ON PLASTIC OR COMPOSITION FLOORS.**

SPECIFICATION:

Appearance	-	Clear colourless liquid
Odour	-	Camphor odour
Specific Gravity	-	0.97
pH	-	Approx. 9.0 (Emulsion)
Safety	-	Completely safe when used as directed

CAUTION: **TAG CONTAINS ORTHODICHLOROBENZENE. INFLAMMABLE LIQUID.**

Avoid contact with skin, eyes and clothing.
Avoid breathing vapour.
Use only in well ventilated areas.
For splashes, irrigate copiously with water.
For eyes, seek medical attention immediately.
Must not be taken internally.

BEST-CHEM LTD. IS AN ISO 9002 REGISTERED FIRM.