

# TECHNICAL DATA SHEET

# TROL 5000

## LIQUID WASTE TREATMENT

**COMPOSITION:** **TROL 5000** is an economical waste control agent to overcome foul odours and prevent oil and fat build-ups comprising of blended solvents with biodegradable emulsifying agents.

**BENEFITS:**  
Controls foul odours.  
Repels flies and insects.  
Disperses oil, grease and fats.  
Dilutes with water.  
Economically dosed by drip feed.

**DIRECTIONS FOR USE:**  
**ODOUR TREATMENT:**  
To remove smells around dustbins, refuse chutes, etc. Dilute **TROL 5000** with up to 50 parts water. Add **TROL 5000** to water stirring vigorously to form a white emulsion. Use immediately by non-atomising spray or watering can. **DO NOT FOG.** For continuous deodorant action in liquid effluents, drip feed or dose a turbulent spot at between 10 and 20 parts per million of **TROL 5000**.

**DEGREASING:**

Use **TROL 5000** neat to dissolve grease and fat deposits, mixing thoroughly to emulsify residues. **DO NOT SPRAY NEAT TROL 5000.**

**GREASE AND FAT CONTROL:**

For continuous control of oil, fat, and grease deposits in liquid effluents, dose **TROL 5000** as close to the source at between 100 and 200 parts per million by drip feed. To disperse fat globules and avoid blockages, add **TROL 5000** whilst agitating. The best effectiveness is obtained in warm water before fat congeals.

**SPECIFICATIONS:**

Appearance	-	Clear pale green liquid
Odour	-	Solvent/Camphor odour
Specific Gravity	-	0.9
pH	-	Approx. 9
Flash Point	-	110 <sup>0</sup> F
Safety	-	Safe when used as directed

**CAUTION:** **TROL 5000 IS A FLAMMABLE LIQUID.**  
Avoid contact with skin, eyes and clothing. (Eye/hand protection must be worn.)  
For splashes, wash liberally with cold water.

***BEST-CHEM LTD. IS AN ISO 9002 REGISTERED FIRM.***